




HDPE Inserts

Product Release

10/18/2010

Inserts For OD Controlled PE 3408 High Density Polyethylene (HDPE)



Ford Insert Stiffeners are solid 304 tubular stainless steel, dimpled and flanged to retain placement within the service line.

Before using Ford insert stiffeners, be sure inside pipe dimensions correspond to the table below.

**NOTE: Consult pipe or tubing manufacturer for specific installation requirements.
Ford recommends using insert stiffeners when using plastic pipe or tubing.**

Inserts For OD Controlled PE 3408 High Density Polyethylene (HDPE)

CATALOG NUMBER	NOMINAL SIZE & PIPE TYPE	DR	HDPE OD	NOMINAL ID
INSERT-51	3/4" CTS	9	0.875	0.68
INSERT-52	1" CTS	9	1.125	0.88
*INSERT-81-200	3/4" CTS	11	0.875	0.71
INSERT-53-72	1" IPS	11	1.315	1.057
INSERT-73-DR11	1-1/4" IPS	11	1.660	1.34
INSERT-74-DR11	1-1/2" IPS	11	1.900	1.53
INSERT-75-DR11	2" IPS	11	2.375	1.92

*Note: Insert-81-200 does not have dimples as shown above.



The Ford Meter Box Co., Inc. 775 Manchester Avenue, P.O. Box 443, Wabash, Indiana, USA 46992-0443
Telephone: 260-563-3171 FAX: 800-826-3487 Overseas FAX: 260-563-0167 <http://www.fordmeterbox.com>

FHDPE